

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

## TECHNICAL DETAILS



Composition	100% Sunbrella solution dyed acrylic			
Finish	Stain-resistant treatment: exclusive Glen Raven formulation. Does not contain PFOS (perfluorooctanyl sulphate)			
Weave	Weave			ISO 7211-1
Weight	270		g/m <sup>2</sup>	ISO 3801
Width	137		cm	EN 1773

## COLOR RESISTANCE

Colour fastness UV	7/8		class /8	ISO 105 B02
Colour fastness weather condition	7/8		class /8	ISO 105 B04
Colour fastness 40°C washing	5		class /5	ISO 105 C06
Colour fastness dry friction	5		class /5	ISO 105X12
Colour fastness wet friction	5		class /5	ISO 105X12

## PHYSICAL CHARACTERISTICS



Fire resistance	Class 1			U.F.A.C.
Oil-repellent properties	5		class /8	ISO 14419
Tensile strength	160	80	daN	ISO 13934-1
Elongation at break	30	30	%	ISO 13934-1
Tear strength	7	3.7	daN	ISO 13937-1
Stitching strength	50	50	daN	ISO 13935-1
Abrasion (Martindale)	15,000 – 25,000 depending on colour		nb cycles	ISO 12947-2
Schmerber	200		mm	ISO 811
Spray test	5		class /5	ISO 4920
Air permeability	65		l/m <sup>2</sup> /s	ISO 9237
Stability on washing (40 °C)	-2	0	%	ISO 5077

## COLORS



## TECHNICAL DETAILS



PROTEGE LA PIEL DE LAS QUEMADURAS SOLARES PARANDO MÁS DE 97% DE LOS RAYOS UV

PROTECTS YOUR SKIN  
BLOCKS MORE THAN 97% OF UV RAYS



CLASE 1 (ARTICULOS PARA BEBÉS)  
ANTI ALERGICO - POLIMERO INERTE

CLASS 1 (ARTICLES FOR BABIES)  
NON ALLERGIC - INERT POLYMER



100% RECICLABLE  
100% RECYCLABLE

Composition	100% Olefin 'COSLAN' from POLISILK
Warp & Weft Count	500 den, solution dyed
Yarns/cm Ends/Inch	22 56
Picks/cm Picks/inch	13 33
Grams/m <sup>2</sup> Ounces/sq. yard	190 5,6
Finish	Water and oil repellent Nuva®

## COLOR FASTNESS

<b>Light Fastness</b> UNE EN ISO 105-B02:2001 Metode 2	7 – 8 (max 8)
<b>Fastness to rubbing</b> UNE EN ISO 105-X12:1996	4 – 5 (max 5)
<b>Swimming Pool water fastness</b> UNE EN ISO 105-E03:1997	5 (max 5)

## PHYSICAL CHARACTERISTICS



EXCELENTE PROTECCIÓN CONTRA LA DEGRADACIÓN POR LA ACCIÓN DEL SOL.

EXCELLENT PROTECTION AGAINST SUNLIGHT DEGRADATION



COLORES TINTADOS EN MASA, OFRECIENDO GRAN SOLIDEZ. NO SE PUORE.

SOLUTION DYED COLORS OFFERS VERY GOOD COLOR STABILITY  
ROT-PROOF



REPELENTE AL AGUA

WATER REPELLENT

	Warp	Weft
<b>Breaking Strength</b> UNE EN ISO 13934-1	1647 N	740 N
<b>Tear Resistance</b> UNE EN ISO 13937-3	73,9 N	43,18 N
<b>Slippage Resistance (seam method)</b> Pr EN ISO 13936-2	3 mm	3 mm
<b>Abrasion Resistance</b> UNE EN ISO 12947 (Part 1 & 2) Modificada según BS 2543:1995	20.000 cycles	
<b>Pilling Resistance</b> UNE EN ISO 12945-2	5 (max 5)	
<b>Dimensional Change in Washing</b> UNE EN 25077:1996	-0,4%	-0,3%
<b>Spraytest</b> UNE EN 24920	5 (max 5)	

## COLORS

